HOLLOWICK LAMP FUEL

USED IN: HD10, HD12TALL, HD26, HD2618HL & HD36TALL **Liquid Candles**

1. IDENTIFICATION OF THE PRODUCT AND OF THE COMPANY UNDERTAKING

Product identifier

Product name Hollowick Lamp Fuel Blend- Used in HD10, HD12TALL, HD26, HD2618HL

& HD36TALL Liquid Candles

Relevant identified uses of the substance and uses advised against

Applications Table Lighting Liquid Candles

Details of the supplier of the safety data sheet

Name Hollowick Inc

Address 100 Fairgrounds Drive

PO BOX 305

Manlius, NY 13104

800-367-3015 (Toll Free) Telephone

Fax 315-682-6948

Contact email info@hollowick.com

Emergency telephone number

Telephone 1-800-424-9300 (CHEMTREC)

Outside US: 24 hours-a-day, 7 days-a-week

1-703-527-3887 (CHEMTREC)

2. HAZARDS IDENTIFICATION

GHS Hazards Aspiration hazard,

Aspiration hazard Category 1

Label elements according to the regulation (EC) no. 1272/2008 (CLP)

Hazard pictograms



Signal word

Hazard statements H304 May be fatal if swallowed and enters airways.

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER or **Precautionary**

statements doctor/physician.

Response P331 Do NOT induce vomiting.

Precautionary P405 Store locked up.

statements - Storage

Precautionary P501 Dispose of contents/container only in accordance with local and

statements - Disposal national regulations.

Other hazards

Emergency overview Contact may cause eye and skin irritation.

For small children a single sip of lamp oil or even sucking the wick may lead

to life-threatening lung damage.

Potential short term

Routes of exposure: Eye, Skin contact, Inhalation, Ingestion. health effects

Eyes: May cause irritation.

Skin: May cause irritation.



HOLLOWICK LAMP FUEL

USED IN: HD10, HD12TALL, HD26, HD2618HL & HD36TALL Liquid Candles

Inhalation: Excessive intentional inhalation may cause respiratory tract irritation and central nervous system effects (headache, dizziness).

Ingestion: May cause stomach distress, nausea or vomiting. Aspiration of material into lungs can cause chemical pneumonitis. May act as a laxative.

Target organs Eyes. Skin.

Chronic effects Prolonged or repeated exposure can cause drying, defatting and dermatitis.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Name	CAS No.	EC No.	Index No.	Concentration	Classification DSD/CLP	Specific concentrations limit
White mineral oil (petroleum)	8042-47-5	232-455-8	-	10-60%	Not classified	
Alkanes, C14-16	90622-46-1	292-448-0	-	30 - 90%	Xn; R65	-
					Asp. 1 H304	-

4. FIRST AID MEASURES

Description of first aid measures

General advice If you feel unwell, seek medical advice (show the label where possible).

Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Avoid contact with eyes and skin. Keep out of reach of

children.

Following eye contact If splashed into eyes, flush with clear water for 15 minutes, or until irritation

subsides. Remove contact lenses, if applicable, and continue flushing.

Obtain medical attention if irritation persists.

Following skin contact Remove contaminated clothing. Launder before reuse. Wash skin with soap

and water. Obtain medical attention if irritation persists. Remove

contaminated clothing. Launder before reuse.

Following inhalation If symptoms develop move victim to fresh air. If breathing has stopped,

administer artificial respiration, and seek medical attention immediately. If indicated, administer cardiopulmonary resuscitation. If symptoms persist,

obtain medical attention.

Following ingestion Do not induce vomiting. If vomiting occurs naturally, have victim lean

forward to reduce risk of aspiration. Never give anything by mouth if victim

is unconscious or is convulsing. Obtain medical attention.

Most important symptoms and effects, both acute and delayed

Prolonged/repetitive skin contact may cause redness, drying, defatting and cracking of the skin.

Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

Indication of any immediate medical attention and special treatment needed

Notes to physician: Symptoms may be delayed.

Medical conditions which may be aggravated by exposure: Sensitive skin. Skin contact may aggravate an existing dermatitis.

Variability Among Individuals: Health studies have shown that many petroleum hydrocarbons pose potential human health risks which may vary from person to person. As a precaution, exposure to liquids, vapors, mists or fumes should be minimized.



HOLLOWICK LAMP FUEL

USED IN: HD10, HD12TALL, HD26, HD2618HL & HD36TALL Liquid Candles

5. FIREFIGHTING MEASURES

Extinguishing media Suitable: Dry chemical, carbon dioxide, foam, steam or water fog

Unsuitable extinguishing

media:

Water streams will scatter liquid and spread fire but may be used

to keep fire-exposed containers and surroundings cool.

Special hazards May create dense smoke during combustion

Fire hazard: Mild fire hazard when heated above its flash point; material must be

preheated before ignition will occur (OSHA Class IIIB).

Advice for firefighters Firefighters should wear full protective clothing including self-contained

breathing apparatus.

Stop source of fuel. Shut off ignition sources. Keep exposed containers

cool with water spray.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Do not touch or walk through spilled material. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep people away from and

upwind of spill/leak. Remove all sources of ignition.

Environmental precautions

Do not discharge into lakes, streams, ponds or public waters.

Methods and material for containment and cleaning

up

Stop leak if you can do so without risk. Prevent entry into waterways,

sewers, basements or confined areas. Contain the spill.

For cleaning up

Before attempting clean up, refer to hazard data given above. Small spills may be absorbed with non-reactive absorbent and placed in suitable, covered, labelled containers. Contact emergency services and supplier for advice. Never return spills in original containers for re-use.

Reference to other sections See precautions in section 7 and 8.

7. HANDLING AND STORAGE

Precautions for safe

handling

Use good industrial hygiene practices in handling this material. When using do not eat or drink. Wash hands before breaks and immediately

after handling the product.

Conditions for safe storage,

including any incompatibilities

Keep out of reach of children. Store in a closed container away from

incompatible materials.

Specific end use(s) Not applicable

HOLTOMICK.

SAFETY DATA SHEET

HOLLOWICK LAMP FUEL

USED IN: HD10, HD12TALL, HD26, HD2618HL & HD36TALL Liquid Candles

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure limit values

Component	Туре	Value
Oil mist	TWA	5 mg/m ³

Exposure controls

Appropriate engineering

controls

General ventilation normally adequate. Use only with ventilation sufficient to prevent exceeding recommended exposure limit. Keep containers and storage containers closed when not in use. Do not store

near heat, sparks, flame or strong oxidants.

Personal protectionRespiratory protection: Where exposure guideline levels may be

exceeded, use an approved NIOSH respirator. Respiratory protection is not required under conditions of normal use. Wear an organic vapor respirator with a mist filter if vapor, mist or spray is generated.

Hand protection: Rubber gloves. Confirm with a reputable supplier first.

 $\underline{\text{Eye protection}}\text{: Eye protection is not required under conditions of normal use. Wear safety glasses with side shields when splashing may}$

occur.

<u>Body protection</u>: Use chemical-resistant apron or other impervious clothing, if needed, to avoid contaminating regular clothing which could

result in prolonged or repeated skin contact.

<u>Hygiene measures</u>: Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. Washing with soap and water after use is recommended as good hygienic practice to prevent possible eye irritation from hand contact. Minimize breathing vapor or mist. Avoid prolonged or repeated contact with skin. Remove

contaminated clothing; launder or dry-clean before reuse.

Environmental exposure

controls

Not available

9. PHYSICAL AND CHEMICAL PROPERTIES

Information of basic physical and chemical properties

Physical stateClear, liquidColorWater whiteOdorOdorlessOdor thresholdNot availablepHNot availableMelting pointNot available

Boiling point 248 - 284°C (478 - 544°F)

Flash point > 93.33°C (>200°F) Evaporation rate Not available Flammability Not available Auto ignition temperature ≥ 204 °C (≥ 400 °F)



HOLLOWICK LAMP FUEL

USED IN: HD10, HD12TALL, HD26, HD2618HL & HD36TALL **Liquid Candles**

Upper/lower flammability

or explosive limits

Lower limit in air, by volume: 0.5% Upper limit in air, by volume: 7%

Explosive properties Oxidizing properties

<0.1 mmHg at 20°C/68°F (API Calculation) Vapor pressure

Not available Not available

Vapor density > 5 (Air = 1)Relative density Not available Solubility in water Negligible **Other Solvents** Not available Partition coefficient (n-Not available

octanol/water)

Decomposition temperature

Not available

Kinematic viscosity less than 20.5 mm2/s measured at 40°C, Viscosity

100 Saybolt Universal Seconds at 100°F

Other information

Specific gravity: < 1

10. STABILITY AND REACTIVITY

Reactivity This product may react with strong oxidizing agents.

Chemical stability Stable under recommended storage conditions. This product is stable

and will not react violently with water.

Possibility of hazardous

reactions

Hazardous polymerization does not occur.

Conditions to avoid Do not mix with other chemicals.

Incompatible materials Strong oxidizers.

Hazardous decomposition

materials

May include and are not limited to: oxides of carbon.

11. TOXICOLOGICAL INFORMATION

Information on toxicological effects

Acute toxicity Oral

 LD_{50} (rat): > 5,000mg/kg

Harmful: May cause lung damage if swallowed. Product has a low order of acute oral and dermal toxicity, but as with most light liquid petroleum hydrocarbons, small amounts aspirated into the lungs during ingestion or vomiting may cause pulmonary injury: aspiration of material into lungs can cause chemical pneumonitis. May act as a laxative. May cause stomach distress, nausea or vomiting.

Inhalation

Alkanes, C_{14-16} : LC_{50} (rat): > 5.8 mg/1

White mineral oil (petroleum): Not available

Excessive intentional inhalation may cause respiratory tract irritation and central nervous system effects (headache, dizziness). Inhalation of

mist or spray may be harmful.

HOLLOWICK LAMP FUEL

USED IN: HD10, HD12TALL, HD26, HD2618HL & HD36TALL **Liquid Candles**

Irritation For the skin: May cause irritation. Prolonged or repeated skin contact

with this product tends to remove skin oils possibly leading to

irritation, reddening of skin progressing to dermatitis.

For the eye: This product may cause slight irritation to the eyes. When tested and evaluated according to FHSA Guidelines (16 CFR 1500.42) using albino rabbits, this product does not demonstrate ocular

irritation potential.

Based on the available information on irritation, the mixture has no Corrosivity

corrosive properties.

Sensitization Not available Mutagenicity Not available

Carcinogenicity Studies indicate no carcinogenic properties.

Toxicity for reproduction Not available

Repeated exposure may cause skin dryness or cracking. Repeated dose toxicity

May be fatal if swallowed and enters airways **Aspiration toxicity**

12. ECOLOGICAL INFORMATION

Toxicity White mineral oil (petroleum):

Fish: Lepomis macrochirus: LC₅₀ (96 h) 10000 mg/L

Alkanes:

Fish (Pimephales promelas): considered relatively non-toxic as demonstrated by a no significant effect at any concentration of the water-soluble fraction of C13-C16 normal paraffins to fathead minnows

and water-fleas.

Algae, Bacteria, Protozoa: low toxicity

Persistence and degradability

Alkanes:

Readily biodegradable. Normal paraffins are removed by volatilization,

sorption to sediment/soil and biodegradation.

OECD Test Guideline 301F (28 d): 82%

Test substance LINPAR 1417

Biodegradation half-lives in water systems range from < 15 to 30 days

(10 day window met)

Not available

Bio accumulative potential

Not available Mobility in soil Not available Results of PBT and vPvB Not available

assessment

13. DISPOSAL CONSIDERATIONS

Other adverse effects

Waste Code Any unused product or empty containers may be disposed of as non-

hazardous in accordance with state and federal requirements

Disposal methods Dispose of only in accordance with local, state, and federal regulations

Empty containers Empty containers retain product residue. Dispose of in the same

manner as the product.

HOLTOMICK.

SAFETY DATA SHEET

HOLLOWICK LAMP FUEL

USED IN: HD10, HD12TALL, HD26, HD2618HL & HD36TALL Liquid Candles

Empty Containers should not be refilled

14. TRANSPORT INFORMATION

General Information Not regulated by U.S. DOT, Canadian TODG, IMO/IMDG, ICAO/IATA, ADR/RID

UN Number -

UN proper shipping name Transport hazard classes Packing group Environmental hazards -

Land transport (ADR/RID) Not regulated
On land waterway craft Not regulated

(ADN/ADNR)

Marine transport (IMDG)

Air transport (IATA)

Special precautions for user

Transport in bulk according

Not available

Not available

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code

15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture Non-European regulations

OSHA Hazards See Section 2

TSCA inventory listing

Component/CAS:

C₁₄₋₁₆ Normal Paraffin / 90622-46-1 Paraffinic White Mineral Oil / 8042-47-5

SARA 302 Status

Component: Contains no chemicals subject to SARA 302 reporting.

SARA 311/312 Classification Innediate (acute) health hazard.

SARA 313 Chemicals

Component: Contains no chemicals subject to SARA 313 reporting.

CERCLA Hazardous Substance (40 CFR 302)

Contains no chemicals on the CERCLA Hazardous Substance list.

Hazard Ratings NFPA

Health: 1 Flammability: 1 Reactivity: 0 Specific hazard: -



HOLLOWICK LAMP FUEL

USED IN: HD10, HD12TALL, HD26, HD2618HL & HD36TALL Liquid Candles



State Regulations

California Prop.65 Components none

Canadian federal regulations

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

WHMIS status: Not Controlled

Domestic Substances List (DSL): Yes

Non-Domestic Substances List (NDSL): No

A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

Chemical safety assessment

A chemical safety assessment has not been conducted on the

substances contained in the mixture by the supplier.

16. OTHER INFORMATION

Date of Publication: June 1st, 2015 reviewed 6-11-2018. / Updated 11-7-19 with new product, Rev 8-31-21

This information is based on our present knowledge and is provided according to the relevant EC and national regulations. This information is intended as a characterization of the product in order to provide guidance for the relevant safety issues. However, this document does not provide any warranty, expressed or implied, regarding the properties of the product.