



StandOut®

Durable Floor Finish

StandOut® Durable Floor Finish is a durable, high performance floor finish with superior resistance to alcohol hand sanitizers.

Features & Benefits

- No mixing required - just squeeze the pouch to break the seal and release the pre-determined amount for a ready-to-use solution
- Twice as durable as conventional floor finish, reducing maintenance frequency
- Hand sanitizer resistant formula maintains high appearance longer
- Reduces chemical waste with unique shut-off technology
- No chemical exposure risks with unique closed-loop packaging
- Minimizes water requirements

Applications

- Apply StandOut® Floor Finish with the Diversey ProSpeed applicator





Use instructions

Preparation

- Hold top portion of the package with two hands and squeeze to rupture seal between components.
- If seal is difficult to rupture, slightly twist or bend the top portion of the package.
- Squeeze the top portion of the bag and agitate the package for 60 seconds to ensure the components are thoroughly mixed.
- Allow 10 minutes before applying to the floor.

Application

- Blockade areas to be stripped or finished.
- Caution, floor will be very slippery until dry.
- Apply to a clean, dry floor, making sure to strip the floor of any previous finish/coating according to label directions.
- Apply 4-5 uniform coats using a ProSpeed™ applicator and clean pad at an application rate between 1800 and 2400 sq. ft. per gallon.
- Allow coating to dry to the touch between coats (about 30 minutes).

Recoating

- Dust mop or sweep.
- Deep scrub floor using recommended Diversey Care brand cleaner according to label directions.

- Apply 1-2 uniform coats using a ProSpeed™ applicator and clean pad.
- Allow coating to dry to the touch between coats (about 30 minutes).

Removal

- For best results, use Diversey Pro Strip™ ULTRA or Attac® ULTRA at a 1:4 dilution and TASKI Hard Nylon Scrub Brush unless substrate requirements differ, in which case follow recommendations for that substrate.
- For linoleum use LinoSAFE® Linoleum Stripper at a 1:4 dilution and a TASKI Soft Nylon Scrub Brush.
- Apply stripping solution to the floor according to label directions and allow to dwell for 5 minutes.
- Scrub the floor using an autoscrubber or swing machine at a slow pace making two passes.
- Allow the stripping solution on the scrubbed floor to dwell for 10 more minutes. Agitate and add more stripping solution as needed to prevent it from drying out.
- Scrub the floor again using an autoscrubber or swing machine at a slow pace until coating is removed (about 7 minutes per 100 sq. ft.).

Technical data	StandOut® Durable Floor Finish
Color/Form	Opaque Colorless Liquid
pH	9.44
Scent	Surfactant
Shelf Life	1 Year

Product	Pack size	Dilution	Product code
StandOut® Durable Floor Finish	4 x 1.5 L Pouch	Ready-to-Use	100880768 

Safe handling

Please make sure your employees read and understand the product label and Safety Data Sheet before using this product. The label contains directions for use; and both the label and SDS contain hazard warnings, precautionary statements and first aid procedures. SDS are available online at www.diversey.com or by calling 888.352.2249. Improper use or dilution may result in damage to surfaces and may result in health and physical hazards that match those of the concentrate.